

IP CCTV / Professional IP cameras / EASY-P / Turret cameras

# EP-IPT210A-2

EasyP



## Features

---

- Easy-P with Artificial Intelligence
- Turret IP Camera
- 1/3" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- 2.8mm lens
- 0 Lux
- IR Range 25 m
- Compression H.264 / H.265 / JPEG / AVI / MJPEG
- 3DNR
- DWDR
- Integrated microphone
- Full compatibility with Uniview and Hikvision
- Supports UMD and Motion Detect 2.0
- ONVIF Compatible
- P2P -PoE (IEEE802.3af)
- Plastic material

## Specifications

---

<b>Brand</b>	EASY-P
<b>Image sensor</b>	1/3" Progressive Scan CMOS
<b>Maximum resolution</b>	2 Megapixel (1920x1080)
<b>Minimum illumination</b>	Colour: 0.04 Lux @(F1.6, AGC ON)
<b>Lens</b>	2.8 mm
<b>Viewing Angle (FOV)</b>	H: 95°, V: 53°, D: 114°
<b>Lighting Scope</b>	IR up to 25m
<b>Day/Night</b>	Removable mechanical ICR filter
<b>Compression</b>	H.264 / H.265 / JPEG / AVI / MJPEG
<b>Electronic Shutter</b>	1/3~1/100000 s
<b>Main Stream rate</b>	1920*1080@30fps 1280*720@30fps
<b>Extra Stream rate</b>	720*480@30fps 640*360@30fps 352*288@30fps
<b>Bitrate</b>	64 Kbps ~ 6 Mbps
<b>Image improvements</b>	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
<b>Motion detection and UMMD</b>	Supports both functions
<b>Smart Features</b>	Native support of Motion Detect 2.0 and UMD
<b>Audio</b>	Integrated microphone
<b>Audio Compression</b>	G711A / U
<b>Network interface</b>	Ethernet 10 / 100M BaseT
<b>Remote access</b>	Web Browser, APP
<b>Interoperability</b>	ONVIF, plug&play with Uniview and Hikvision
<b>P2P</b>	Yes
<b>Power</b>	DC 12 V / 9 W max. PoE IEEE802.3af
<b>Material</b>	Plastic

**Temp. operation** -20° C ~ +60° C

---

**Dimensions** 109.3 (Ø) x 95.2 (h) mm

---

**Weight** 242 g

---